

## AML-6

The AML-6 series of instruments is a highly configurable family of multiparameter sondes designed for a wide range of data collection applications. The '6' designation refers to the number of X2 series sensors that may be simultaneously installed on the instrument's endcap. Additional sensors may be connected externally, allowing up to 8 sensors in total.

The AML-6 comes in the AML-6 LGR and the AML-6 RT. While nearly identical in size and form factor, the two configurations differ in a few key features which specialize them for their respective applications:

- The LGR designation (ie. AML-6 LGR) are self-powered via a rechargeable internal battery and have a mechanical on/off switch adjacent to their shackle. These instruments are most commonly used for multiparameter profiling applications and internally log sensor measurements and transfer data postdeployment.
- The RT designation (ie. AML-6 RT) stream data while in-situ (though they have the ability to internally record data as well). Power and communication to these instruments is facilitated via a waterproof connector located adjacent to the shackle. These instruments rely on external power for operation and the application of this power turns the instrument on in lieu of a mechanical switch These instruments are commonly used in moored applications, buoys, underwater observatories, and ROVs.







**GPS** 









Depth Rating

Depth Rating



Max. Depth	500m	6000m
Number of Ports	6 (Option for up to 8)	6 (Option for up to 8)
Biofouling Protection	Street Lamp UV	N/A
Communication	WiFi, USB-C, RS232	USB-C, RS-232
Input Voltage	8-30 VDC	8-30 VDC
Pressure Housing	Acetal	Steel Reinforced Acetal
Protective Cage	Stainless Steel (Optional: CuNi)	Stainless Steel (Optional: CuNi)
Dimensions	600 x 100 mm	600 x 100 mm
Weight in Air	4.0 kg	4.9 kg
Weight in Water	2.1 kg	2.8 kg
Software	Sailfish	Sailfish

## **Key Benefits:**

- **Six X2 series Interchangeable Ports:** Ability to custom configure a single instrument for multiple applications
- Magnetic On/Off Switch: Configure Now, Power & DeployLater
- Integrated WiFi & GPS: Transfer data wirelessly
- **USB Connectivity:** Recharge battery and connect via USB
- Integrated UV Biofouling (Optional): Maintain consistent data quality & Decrease maintenance intervals
- Sailfish Software: Download, process, and export profiles automatically